



The BluFi's coaster pagers notify customers with a beep, flash or vibration the instant their meal is ready.

Lightweight commercial strength Pagers allow your customers to visit the Bar or nearby areas for a more relaxing experience while they wait for their meal.

- Wall mount case dor pager, buttons, buzzer and external LEDS.
- 2 screw holes at back panel for easy, telephone like, installation.
- 220V inlet, (RJ11 connector).
- Internal rechargeable battery backup.
- External antenna.
- Loud buzzer.
- Strong display illumination.
- Automatic illumination display: Light on when reading.
- Out of range LED indicator.
- Emergency message LED.
- Normal message LED.
- New message autoscroll N times.
- Function Menu Disabled.
- Pager always on.
- Pager always buzzer alert (Vibrato disabled, mute disabled).
- Pager Fixed Display Brightness.
- Time & Date set/updates by OTA.
- 8/4 lines change by single fuction button press (toggle button).

Specifications

Frequency Range:	UHF: 454-462MHz
Cap Codes:	4
Receiver Type:	Synthesized
Baud Rate:	512, 1200, 2400 bps
Paging Sensitivity	5 μ V/m @ 512 bps 7 μ V/m @ 1200 bps 9 μ V/m @ 2400 bps
Channel Spacing:	20KHz / 25KHz
Frequency Deviation:	+/-4.5KHz
Frequency Stability:	+/- 10 ppm
Selectivity:	> 60dB
Image Rejection:	Better than 50dB
Spurious Rejection:	Better than 50dB
Intermodulation:	Better than 50dB
Alert Tone Loudness:	Vibration, Beeping, Flashing
Display:	7 segment x 3 digit Backlight, numeric and icons
Memory Capacity:	more than 10 minutes
Messages:	20 characters per cap code
Weight:	122 g with battery (4.3 oz)
Dimensions:	105 x 18 mm 4.1 x 0.7 inch
Battery Type:	Custom Ni-Mh 2.4 volt
Low Battery Alert Level:	1.1V
Operating Temperature:	-28° to 68° C

*Other frequencies available upon request

