



Wall mounted 8/4 line alphanumeric pager with auto scroll.

Big display with strong illumination with zoom to switch from 8 to 4 lines.

- Wall mount case dor pager, buttons, buzzer and external LEDES.
- 2 screw holes at back panel for easy, telephone like, installation.
- 120V inlet, (RJ11 connector).
- Internal rechargeable battery backup.
- External antenna.
- Loud buzzer.
- Strong display illumination.
- Automatic illumination display: Light on when reading.
- Out of range LED indicator.
- Emergency message LED.
- Normal message LED.
- New message autoscroll N times.
- Function Menu Disabled.
- Pager always on.
- Pager always buzzer alert (Vibrato disabled, mute disabled).
- Pager Fixed Display Brightness.
- Time & Date set/updates by OTA.
- Zoom 8/4 lines, switch by just pressing one button (toggle button).

Specifications

Frequency Range*:	VHF: 143-150MHz 151-159MHz 159-167MHz UHF: 454-460MHz 460-466MHz
Cap Codes:	8
Receiver Type:	Synthesized
Baud Rate:	512, 1200, 2400 bps
Paging Sensitivity	5uV/m @ 512 bps 7 uV/m @ 1200 bps 9uV/m @ 2400 bps
Channel Spacing:	25KHz
Frequency Deviation:	+/-4.5KHz
Frequency Stability:	+/- 7ppm
Selectivity:	> 55dB
Image Rejection:	> 52dB
Spurious Rejection:	> 57dB
Intermodulation:	> 52dB
Alert Tone Loudness:	95db+ @ 12 inch
Display:	small fonts: 21 characters x 8 lines large fonts: 17 characters x 4 lines
Memory Capacity:	20,000 English characters
Private Messages:	60 (30 of which protectable)
Weighth:	65 g with battery (2.3oz)
Dimensions:	75 x 51 x 18 mm 3 x 2 x 0.7 inch
Battery Type:	2 AAA rechargeable batteries + external power supply
Low Battery Alert Level:	1.1V
Operating Temperature:	-10° to 50° C

*Other frequencies available upon request

